


## BIT BASICS



## A SHANK BIT PARTS

- 1 CHEEK
- 2 PURCHASE
- 3 SHANK
- 4 MOUTHPIECE
- 5 PORT

## B HOW TO MEASURE A SHANK BIT

## 1 Mouthpiece Measurement:



Traditional Shank Bits are measured laying flat as shown. Mouthpiece measurement is taken from one cheek to the other cheek as shown.

Myler Bits™ mouthpieces are measured with a curve in the mouthpiece as shown in (A).

Always allow 1/8" to 1/4" extra mouthpiece outside the horse's lips on each side.

## 2 Cheek Measurement:

Cheeks are measured from the top inside of the purchase ring straight down to the same plane as the center inside of the rein ring. This measures the difference from the headstall to the rein when the horse is bridled.



## C RING BIT PARTS

- 1 CHEEK OR RING
- 2 MOUTHPIECE
- 3 JOINT

## D HOW TO MEASURE A RING BIT

## 1 Mouthpiece Measurement:

Traditional Ring Bits are measured laying flat as shown. Mouthpiece measurement is taken from one cheek to the other cheek as shown.

Myler Bits™ mouthpieces are measured with a curve in the mouthpiece as shown in (C).

Always allow 1/8" to 1/4" extra mouthpiece outside the horse's lips on each side.

## 2 Ring Measurement:

Rings are measured from the top outside of the ring to the bottom outside of the ring.

